



GREENBALL[®]
TIRES FOR THE ROAD, WORK, AND PLAY

2020 CATALOG



www.greenballtires.com

TABLE OF CONTENTS

LIGHT TRUCK RADIAL	2-8
SPECIAL TRAILER RADIAL	9-12
SPECIAL TRAILER RADIAL ASSEMBLIES	13
SPECIAL TRAILER BIAS	14-16
LPT/MOBILE HOME	17
SPECIAL TRAILER BIAS TIRE AND WHEEL ASSEMBLIES	18-19
LAWN AND GARDEN	20-23
GOLF CART	24
GOLF CART TIRE AND WHEEL ASSEMBLIES	25
ATV/UTV TIRES	26-38
ALUMINUM AND STEEL TRAILER WHEELS	39-43
MOBILE HOME WHEELS	44
GOLF CART WHEELS	45
TRAILER WHEEL ACCESSORIES	46



GREENBALL[®]
TIRES FOR THE ROAD, WORK, AND PLAY



KANATI[®]
QUALITY PERFORMANCE TIRES





MAXIMUM DURABILITY

12-ply rated All-Steel construction for heavy-duty towing and payloads.

AGGRESSIVE A/T DESIGN

Engineered for optimum traction in a variety of terrains.

QUIET RIDE

Comfortable for everyday driving. A beast without the roar.



**ALL-STEEL
CONSTRUCTION
FOR THE STRENGTH
THE ROAD DEMANDS**

Available in 28 sizes for 17"-20" wheel sizes.
Made in Indonesia.

ARMOR HOG ATX
www.kanatitires.com

**KANATI® ARMOR HOG ATX****ALL-STEEL CONSTRUCTION FOR SUPERIOR STRENGTH AND DURABILITY**

- 12-ply rated All-Steel construction for heavy-duty towing and payloads
- Engineered for optimum traction in a variety of terrains
- Quiet and comfortable ride for everyday driving
- Excellent impact and puncture resistance

KANATI ARMOR HOG ATX LIGHT TRUCK RADIAL

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/ SPEED RATING	MAX LOAD SINGLE/DUAL
LA1723580F	LT235/80R17	12PR	18	31.9	9.2 on 6.5	6.0 - 7.5	58.2	95	123/120Q	3415/3085
LA1724570F	LT245/70R17	12PR	18	30.7	9.7 on 7.0	6.5 - 8.0	57.4	95	122/119Q	3305/3000
LA1724575F	LT245/75R17	12PR	18	31.6	9.7 on 7.0	6.5 - 7.5	59.5	95	124/121Q	3525/3195
LA1726570F	LT265/70R17	12PR	18	31.8	10.71 on 8	7.0 - 8.5	62.7	95	126/123Q	3750/3415
LA1728570F	LT285/70R17	12PR	18	32.9	11.5 on 8.5	7.5 - 9.0	68.5	95	129/126Q	4080/3750
LA1729570F	LT295/70R17	12PR	18	33.4	11.7 on 8.5	7.5 - 10.0	71.2	95	129/126Q	4080/3750
LA1730570F	LT305/70R17	12PR	18	34	12.2 on 9	8.0 - 9.5	75.1	80	129/126Q	4080/3750
LA1731570F	LT315/70R17	12PR	18	34.5	12.7 on 9.5	8.0-11.0	77.6	80	129/126Q	4080/3750
LA1733125F	33x12.50R17LT	12PR	18	32.7	12.5 on 10	8.5 - 11.0	72.9	80	124Q	3525
LA1735125F	35x12.50R17LT	12PR	18	34.7	12.5 on 10	8.5 - 11.0	77.9	80	129Q	4080
LA1737125F	37x12.50R17LT	12PR	18	36.7	12.5 on 10	8.5 - 11.0	85.8	80	129Q	4080
LA1826570F	LT265/70R18	12PR	18	32.7	10.7 on 8	7.0 - 9.0	66.6	95	127/124Q	3860/3525
LA1827565F	LT275/65R18	12PR	18	32.2	10.9 on 8	7.5 - 9.0	65.6	95	127/124Q	3860/3525
LA1827570F	LT275/70R18	12PR	18	33.3	10.9 on 8	7.0 - 9.0	69.0	95	129/126Q	4080/3750
LA1828570F	LT285/70R18	12PR	18	33.9	11.5 on 8.5	7.5-9.5	72.7	95	129/126Q	4080/3750
LA1829570F	LT295/70R18	12PR	18	34.4	11.7 on 8.5	8.0-10.0	TBA	95	129/126Q	4080/3750
LA1830570F	LT305/70R18	12PR	18	35	12.2 on 9	8.5 - 10.0	79.4	80	129/126Q	4080/3750
LA1835125F	35x12.50R18LT	12PR	18	34.7	12.5 on 10	8.5 - 11.0	78.9	80	128Q	3970
LA1837125F	37x12.50R18LT	12PR	18	36.7	12.5 on 10	8.5 - 11.0	84.9	80	128Q	3970
LA2026560F	LT265/60R20	12PR	18	32.7	10.7 on 8	7.5 - 9.5	67.0	95	125/122Q	3640/3305
LA2027560F	LT275/60R20	12PR	18	33.3	10.9 on 8	7.5 - 9.5	69.1	95	127/124Q	3860/3525
LA2027565F	LT275/65R20	12PR	18	34.3	10.9 on 8	7.5 - 9.5	71.3	95	129/126Q	4080/3750
LA2028560F	LT285/60R20	12PR	18	33.8	11.5 on 8.5	8.0 - 10.0	72.6	95	129/126Q	4080/3750
LA2029560F	LT295/60R20	12PR	18	34.3	11.7 on 8.5	8.0 - 10.0	TBA	95	129/126Q	4080/3750
LA2032560F	LT325/60R20	12PR	18	35.4	13 on 9.5	9.0 - 12.0	84.8	80	129/126Q	4080/3750
LA2033125F	33x12.50R20LT	12PR	18	32.7	12.5 on 10	8.5 - 11.0	73.3	80	119Q	3000
LA2035125F	35x12.50R20LT	12PR	18	34.7	12.5 on 10	8.5-11	TBA	80	125Q	3640
LA2037125F	37x12.50R20LT	12PR	18	36.7	12.5 on 10	8.5 - 11.0	84.9	80	128Q	3970



KANATI® MUD HOG M/T

EXCELLENT TRACTION AND PERFORMANCE

- High quality, durable construction
- Aggressive angle tread design for superior traction
- Optimized void ratio for effective clean-out
- Engineered for on and off-road performance
- 3-ply sidewalls for increased strength and puncture resistance

KANATI MUD HOG M/T LIGHT TRUCK RADIAL

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/ SPEED RATING	MAX LOAD SINGLE/DUAL
L1531105C-252*	31X10.5R15LT	6PR	19	30.8	10.9 on 8.5	7-9	47.5	50	109Q	2270
L153510C-252*	35X10R15LT	6PR	20	34.7	10.0 on 8	7-8.5	62.0	50	118Q	2910
L1535125C-252*	35X12.50R15LT	6PR	20	34.8	12.5 on 10	8.5-11	62.1	35	113Q	2535
L1623585E-252	LT235/85R16	10PR	18	32.0	9.3 on 6.5	6-7.5	51.0	80	120/116Q	3042/2778
L1624575E-252	LT245/75R16	10PR	18	30.7	9.8 on 7	6.5-8	49.9	80	120/116Q	3042/2778
L1626575E-252	LT265/75R16	10PR	18	31.9	10.5 on 7.5	7-8	54.2	80	123/120Q	3415/3085
LH1628575E-252	LT285/75R16	10PR	19	33.0	11.3 on 8	7.5-9	60.2	80	126/123Q	3750/3415
LH1630570E-252	LT305/70R16	10PR	20	33.1	12.2 on 9	8-9.5	64.8	65	124/121Q	3525/3195
L1631575D-252*	LT315/75R16	8PR	20	34.8	12.3 on 8.5	8-11	63.7	50	121/118Q	3195/2910
L1726570E-252	LT265/70R17	10PR	18	31.9	10.7 on 8	7-8.5	54.2	80	121/118Q	3195/2910
L1728570E-252	LT285/70R17	10PR	19	33.0	11.5 on 8.5	7.5-9	61.4	80	123/120Q	3465/3120
L1729570E-252	LT295/70R17	10PR	19.7	33.5	11.8 on 8.5	7.5-10	60.9	80	121/118Q	3195
L1730570E-252	LT305/70R17	10PR	19.7	34.1	12.3 on 9.0	8-9.5	65.0	80	121/118Q	3195
L1731570E-252	LT315/70R17	10PR	19.7	34.6	12.7 on 9.5	8-11	65.6	80	121/118Q	3195
L1733125E-252	33X12.50R17LT	10PR	19	32.8	12.5 on 10	8.5-11	59.9	80	120Q	3085
L1735125E-252	35X12.50R17LT	10PR	20	34.8	12.5 on 10	8.5-11	64.3	80	121Q	3195
L1737125E-252	37X12.50R17LT	10PR	19	36.8	12.5 on 10	8.5-11	72.7	80	124Q	3525
L1739125E-252	39X12.50R17LT	10PR	21	38.8	12.8 on 10	8.5-11	85.0	65	128Q	3970
L1827565E-252	LT275/65R18	10PR	20	32.3	11 on 8	7.5-9	57.0	80	123/120Q	3415/3085
L1827570E-252	LT275/70R18	10PR	19	33.4	10.9 on 8	7-8.5	59.0	80	125/122Q	3640/3305
LH1830570E-252	LT305/70R18	10PR	20	35.1	12.2 on 9	8-10	67.4	80	126/123Q	3750/3415
L1833125E-252	33X12.50R18LT	10PR	20	32.6	12.6 on 10	10	62.2	80	118Q	2910
L1835125E-252	35X12.50R18LT	10PR	20	34.8	12.6 on 10	10	67.1	80	123Q	3415
L2027560E-252	LT275/60R20	10PR	20	33.0	11 on 8	9	59.1	80	123/120Q	3415/3085
L2027565E-252	LT275/65R20	10PR	19	34.3	11 on 8.0	7.5-9.5	60.0	80	126/123Q	3750/3415
L2029560E-252	LT295/60R20	10PR	20	34.0	12 on 8.5	8-10	66.2	80	126/123Q	3750/3415
L2033125E-252	33X12.50R20LT	10PR	19	32.7	12.5 on 10	8.5-11	61.4	80	114Q	2600
L2035125E-252	35X12.50R20LT	10PR	20	35.0	12.5 on 8.5	8.5-11	66.6	80	121Q	3195
L2037125E-252	37X12.50R20LT	10PR	20	37.0	12.5 on 10	8.5-11	71.5	80	126Q	3750
L2039135E-252	39X13.50R20LT	10PR	21	38.8	13.6 on 11	8.5-11	83.8	65	128Q	3970
L2233125E-252	33X12.50R22LT	10PR	20	32.8	12.50 on 10	8.5 - 11	60.2	80	109Q	2270
L2235125E-252	35X12.50R22LT	10PR	20	34.7	12.5 on 10	8.5-11	66.1	80	117Q	2835
L2237135E-252	37X13.50R22LT	10PR	20	36.7	13.6 on 11	8.5 - 11	75.0	80	123Q	3415
L2239145E-252	39X14.50R22LT	10PR	21	38.8	14.6 on 12	10-12	87.0	65	128Q	3970

*2-ply sidewall construction

**KANATI®****TRAIL HOG A/T-4****ALL TERRAIN / ALL WEATHER / SUPERIOR TRACTION**

- Mountain snow flake rated
- Winter stud compatible using #16 studs
- Superior traction and control
- Smooth and quiet ride
- Tough 3-ply sidewall construction

**KANATI TRAIL HOG A/T-4 LIGHT TRUCK RADIAL**

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/ SPEED RATING	MAX LOAD SINGLE/DUAL
LTH1626575E	LT265/75R16	10PR	18	31.8	10.7 on 7.5	7-8	52.3	80	123/120Q	3415/3085
LTH1628575E	LT285/75R16	10PR	18	32.9	11.5 on 8.0	7.5 - 9.0	52.3	80	126/123Q	3750/3415
LTH1723580E	LT235/80R17	10PR	18	31.9	9.2 on 6.5	6-7.5	48.2	80	120/117Q	3085/2835
LTH1724570E	LT245/70R17	10PR	18	30.6	9.8 on 7	6.5-8.0	47.4	80	119/116Q	3000/2755
LTH1724575E	LT245/75R17	10PR	18	31.6	9.8 on 7	6.5-7.5	49.2	80	121/118Q	3195/2910
LTH1726570E	LT265/70R17	10PR	18	31.7	10.6 on 8	7-8.5	52.1	80	121/118Q	3195/2910
LTH1728570E	LT285/70R17	10PR	18	32.8	11.5 on 8.5	7.5-9	57.0	80	123/120Q	3465/3120
LTH1730570E	LT305/70R17	10PR	18	34	12.3 on 9	8-9.5	63.3	80	121/118Q	3195/2910
LTH1731570E	LT315/70R17	10PR	18	34.5	12.7 on 9.5	8-11	65.4	80	121/118Q	3195/2910
LTH1735125E	35X12.50R17LT	10PR	18	34.6	12.8 on 10	8.5-11	64.5	80	121Q	3195
LTH1737125E	37X12.50R17LT	10PR	18	36.7	13.0 on 10	8.5-11	72.5	80	124Q	3525
LTH1826570E	LT265/70R18	10PR	18	32.7	10.7 on 8	7-9	54.3	80	124/121Q	3525/3195
LTH1827565E	LT275/65R18	10PR	18	32.3	10.9 on 8	7.5-9	55.0	80	123/120Q	3415/3085
LTH1827570E	LT275/70R18	10PR	18	33.4	10.9 on 8	7-8.5	57.3	80	125/122Q	3640/3305
LTH1830570E	LT305/70R18	10PR	18	34.9	12.4 on 9	8.5-10	67.1	80	126/123Q	3750/3415
LTH1837125E	37X12.50R18LT	10PR	18	36.7	12.9 on 10	8.5-11	72.1	80	128Q	3970
LTH2026560E	LT265/60R20	10PR	18	32.5	10.7 on 8	7.5-9.5	55.2	80	121/118Q	3195/2910
LTH2027555E	LT275/55R20	10PR	18	32	11.2 on 8.5	7.5-9.5	55.5	80	120/117Q	3085/2835
LTH2027560E	LT275/60R20	10PR	18	33	11 on 8	7.5-9.5	57.1	80	123/120Q	3415/3085
LTH2027565E	LT275/65R20	10PR	18	34.3	10.8 on 8	7.5-9.5	59.2	80	126/123Q	3750/3415
LTH2028560E	LT285/60R20	10PR	18	33.5	11.5 on 8.5	8-10	59.8	80	125/122Q	3640/3305
LTH2030555E	LT305/55R20	10PR	18	33.3	12.4 on 9.5	8.5-10	63.4	80	121/118Q	3195/2910
LTH2032560E	LT325/60R20	10PR	18	35.4	13.1 on 9.5	9-12	71.2	80	126/123Q	3750/3415
LTH2035125E	35X12.50R20LT	10PR	18	34.7	12.5 on 10	8.5-11	66.6	80	121Q	3195
LTH2037125E	37X12.50R20LT	10PR	18	36.7	12.7 on 10	8.5-11	71.3	80	126Q	3750



DIRT COMMANDER M/T

BUILT TOUGH FOR ANY DESTINATION

- Aggressive tread pattern for optimum traction in various rough terrains
- Broader shoulder lugs provide sidewall protection and extra biting edges
- Wider contact patch for even wear and greater longevity
- Equipped with stone ejectors for efficient clean-out



CENTENNIAL DIRT COMMANDER M/T LIGHT TRUCK RADIAL

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/ SPEED RATING	MAX LOAD SINGLE/DUAL
TCD1523575C	LT235/75R15	6PR	18	29.1	9	6.5	40.1	50	104/101Q	1984/1819
TCD1531105C	31X10.50R15LT	6PR	17	30.7	10.5	8.5	45.9	50	109Q	2271
TCD1533125C	33X12.50R15LT	6PR	19	32.8	12.5	10	57.1	35	108Q	2205
TCD1623585E	LT235/85R16	10PR	16	31.7	9.3	6.5	44.9	80	120/116N	3086/2756
TCD1624575E	LT245/75R16	10PR	15	30.5	9.5	7	45.1	80	120/116N	3086/2756
TCD1626575E	LT265/75R16	10PR	16	31.9	10.1	7.5	47.3	80	123/120N	3417/3086
TCD1628575E	LT285/75R16	10PR	17	33.1	11.3	8	52.5	80	126/123N	3748/3417
TCD1723580E	LT235/80R17	10PR	18	32.0	9.4	6.5	44.5	80	120/117Q	3086/2833
TCD1724575E	LT245/75R17	10PR	18	31.7	9.5	7	46.3	80	121/118Q	3195/2910
TCD1726570E	LT265/70R17	10PR	16	31.9	10.9	8	45.5	80	121/118Q	3195/2910
TCD1728570E	LT285/70R17	10PR	17	33.0	11.3	8.5	53.5	80	121/118Q	3195/2910
TCD1729570E	LT295/70R17	10PR	17	33.5	11.8	8.5	56.0	80	121/118Q	3195/2910
TCD1733125D	33X12.50R17LT	8PR	19	32.8	12.7	10	56.7	50	114Q	2601
TCD1735125E	35X12.50R17LT	10PR	18	34.8	12.7	10	63.6	80	121Q	3197
TCD1735125F	35X12.50R17LT	12PR	18	34.8	12.7	10	63.6	80	121Q	3195
TCD1827565E	LT275/65R18	10PR	18	32.3	10.9	8	50.3	80	123/120Q	3417/3086
TCD1827570E	LT275/70R18	10PR	17	33.4	11	8	53.0	80	121/118Q	3195/2190
TCD1833125F	33X12.50R18LT	12PR	19	32.8	12.5	10	60.0	80	122Q	3305
TCD1835125F	35X12.50R18LT	12PR	18	34.8	12.5	10	66.5	80	128Q	3970
TCD2033125F	33X12.50R20LT	12PR	19	32.8	12.5	10	58.5	80	119Q	3000
TCD2035125F	35X12.50R20LT	12PR	18	34.8	12.5	10	62.0	80	125Q	3640
TCD2037125F	37X12.50R20LT	12PR	19	36.8	12.5	10	73.0	80	129Q	4080
TCD2233125F	33X12.50R22LT	12PR	19	32.8	12.5	10	57.2	80	114Q	2600
TCD2235125F	35X12.50R22LT	12PR	18	34.8	12.5	10	63.0	80	121Q	3195
TCD2237135F	37X13.50R22LT	12PR	19	36.8	13.6	11	76.0	80	127Q	3860

NAVPOINT HTX

CENTENNIAL'S NEW VERSATILE ALL-SEASON TIRE

The new Centennial NAVPOINT HTX is a superior all-season highway-terrain tire made for light trucks, SUVs, and CUVs. Suitable for everyday or long-distance travel, its feature-enhanced tread provides drivers with a smooth ride, excellent traction, and greater responsiveness in adverse weather conditions.

20 SIZES

16"-22"

4 YEAR

MANUFACTURER
WARRANTY



Manufactured
in Thailand

**CIRCUMFERENTIAL GROOVES
FOR IMPROVED WATER EXPULSION**

**AGGRESSIVE CENTER TREAD FOR
INCREASED TRACTION IN ADVERSE
CONDITIONS**

**MULTIPLE ANGLED GROOVES FOR
ENHANCED TRACTION IN RAIN
OR SNOW**

**CLOSED SHOULDER DESIGN FOR
RELIABLE HANDLING AND
GREATER STABILITY**



THE FREEDOM TO DRIVE ANYWHERE



NAVPOINT HTX

ALL SEASON PERFORMANCE

- Superior highway terrain tire for everyday driving in all seasons
- Excellent traction in varying weather and road conditions
- Two large circumferential grooves expel water for improved traction on wet roads
- Enhanced with performance siping for tread flex and expansion when needed
- Engineered for driver comfort and low road noise



CENTENNIAL NAVPOINT HTX LIGHT TRUCK RADIAL

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX / SPEED RATING	MAX LOAD SINGLE/DUAL
TNV1622575E	LT225/75R16	10PR	16	29.3	8.8	6	40.2	80	115/112Q	2680/2470
TNV1623585E	LT235/85R16	10PR	16	31.7	9.3	6.5	45.7	80	120/116R	3042/2778
TNV1624575E	LT245/75R16	10PR	16	30.5	9.8	7	43.9	80	120/116S	3042/2778
TNV1626575E	LT265/75R16	10PR	16	31.7	10.5	7.5	49.2	80	123/120R	3415/3085
TNV1628575E	LT285/75R16	10PR	16	32.8	11.3	8	54.6	80	126/123R	3750/3415
TNV1723580E	LT235/80R17	10PR	16	31.8	9.3	6.5	45.9	80	120/117R	3085/2835
TNV1724570E	LT245/70R17	10PR	16	30.6	9.8	7	45.0	80	119/116R	3000/2755
TNV1724575E	LT245/75R17	10PR	16	31.5	9.8	7	46.20	80	121/118S	3195/2910
TNV1725570SL	P255/70R17	SL	14	31.1	10.2	7.5	40.9	44	110T	2337
TNV1726570E	LT265/70R17	10PR	16	31.7	10.7	8	49.6	80	121/118S	3195/2910
TNV1728570E	LT285/70R17	10PR	16	32.8	11.5	8.5	55.8	80	121/118S	3195/2910
TNV1825565SL	255/65R18	SL	14	31.1	10.1	7.5	41.9	44	111T	2403
TNV1826560SL	265/60R18	SL	14	30.5	10.7	8	41.8	44	110H	2335
TNV1827565E	LT275/65R18	10PR	16	32.1	11.0	8	54.2	80	123/120S	3415/3085
TNV1827570E	LT275/70R18	10PR	16	33.2	11.0	8	55.2	80	125/122R	3640/3305
TNV2025555XL	255/55R20	XL	14	31.0	10.4	8	42.7	50	110H	2337
TNV2026560E	LT265/60R20	10PR	16	32.5	10.7	8	54.7	80	121/118S	3195/2910
TNV2027555XL	275/55R20	XL	14	31.9	11.2	8.5	45.4	50	117H	2835
TNV2027565E	LT275/65R20	10PR	16	34.1	11.0	8	57.6	80	126/123R	3750/3415
TNV2228545XL	285/45R22	XL	13	32.1	11.2	9.5	44.1	50	114H	2601

Specifications are factory estimated. Final production specifications to be determined.

**TERRA TROOPER A/T****BUILT FOR A QUIET AND SMOOTH RIDE**

- Aggressive all-terrain tread design
- Tough steel-belted construction
- Full spiral nylon overlay for added strength
- Improved tread angle for excellent traction
- Designed for long tread life
- M & S rated

CENTENNIAL TERRA TROOPER A/T LIGHT TRUCK RADIAL

PART #	SIZE	PLY RATING	TD 32nd INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/SPEED RATING	MAX LOAD SINGLE/DUAL
TTC1531105C	LT31X10.5R15	6PR	15	30.5	10.6	7-9	46.7	50	109S	2270
TTC1621585E	LT215/85R16	10PR	14	30.4	8.5	5.5-7	39.1	80	115/112Q	2680/2470
TTC1621585F	LT215/85R16	12PR	14	30.4	8.5	5.5-7	39.1	95	119/116Q	3000/2755
TTC1622575E	LT225/75R16	10PR	14	29.3	8.8	6-7	39.1	80	115/112Q	2680/2470
TTC1622575F	LT225/75R16	12PR	14	29.3	8.8	6-7	39.1	95	119/116Q	3000/2755
TTC1623585E	LT235/85R16	10PR	15	31.70	9.3	6-7.5	44.4	80	120/116Q	3042/2778
TTC1623585F	LT235/85R16	12PR	15	31.7	9.3	6-7.5	44.4	95	123/120Q	3415/3085
TTC1624575F	LT245/75R16	12PR	15	30.5	9.7	6.5-8	43.7	95	123/120Q	3415/3085
TTC1626575E	LT265/75R16	10PR	15	31.7	10.5	7-8	47.8	80	123/120Q	3415/3085
TTC1626575F	LT265/75R16	12PR	15	31.7	10.5	7-8	47.8	95	126/123Q	3750/3415
TTC1628575E	LT285/75R16	10PR	16	32.8	11.6	7.5-9	56.9	80	126/123R	3750/3415
TTC1628575F	LT285/75R16	12PR	16	32.8	11.6	7.5-9	56.9	95	128/125S	3970/3640
TTC1723580E	LT235/80R17	10PR	16	31.8	9.3	6-7.5	45.5	80	120/117R	3085/2835
TTC1723580F	LT235/80R17	12PR	16	31.8	9.3	6-7.5	45.5	95	121/118S	3195/2910
TTC1724570E	LT245/70R17	10PR	16	30.8	9.8	7	45.2	80	119/116S	2998/2756
TTC1724570F	LT245/70R17	12PR	16	30.8	9.8	7	45.2	95	121/118S	3195/2910
TTC1724575E	LT245/75R17	10PR	16	31.7	9.8	7	48.5	80	121/118R	3197/2910
TTC1724575F	LT245/75R17	12PR	16	31.7	9.8	7	48.5	95	123/120S	3415/3085
TTC1726570E	LT265/70R17	10PR	16	31.7	10.7	7-8.5	49.8	80	121/118S	3195/2910
TTC1726570F	LT265/70R17	12PR	16	31.7	10.7	7-8.5	49.9	95	124/121S	3525/3195
TTC1728570E	LT285/70R17	10PR	16	32.8	11.5	7.5-9	53.7	80	121/118S	3195/2910
TTC1728570F	LT285/70R17	12PR	16	32.8	11.5	7.5-9	53.7	95	126/123S	3750/3415
TTC1827565E	LT275/65R18	10PR	16	32.1	11	7.5-9	51.6	80	123/120S	3415/3085
TTC1827565F	LT275/65R18	12PR	16	32.1	11.0	7.5-9	51.6	95	126/123S	3750/3415
TTC1827570E	LT275/70R18	10PR	16	33.4	11	8	58.6	80	125/122S	3640/3305
TTC1827570F	LT275/70R18	12PR	16	33.4	11.0	8	58.6	95	128/125S	3970/3640
TTC1828565E	LT285/65R18	10PR	16	32.8	11.5	8.5	59.1	80	125/122S	3638/3307
TTC1828565F	LT285/65R18	12PR	16	32.8	11.5	8.5	59.1	95	128/125S	3970/3640
TTC2027565E	LT275/65R20	10PR	16	34.3	11	8	57.32	80	126/123S	3748/3417
TTC2027565F	LT275/65R20	12PR	16	34.3	11.0	8	57.3	95	128/125S	3970/3640

10-ply rated sizes available in limited quantities.



TOW-MASTER ASC[®]

ALL-STEEL CONSTRUCTION SPECIAL TRAILER

- All-Steel construction in both sidewall and tread provides durability under heavy loads
- Stronger casing adds strength and reduces trailer sway
- Five rib design provides large footprint for long life and even wear
- Wide grooves decrease hydroplaning and rolling resistance

15" and 16"
Heavy Duty Aluminum Wheels Available
 See page 39 for details

TOW-MASTER ASC SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/SPEED RATING	MAX LOAD SINGLE/DUAL
THF1522575F	ST225/75R15	LRF	12	28.3	8.8	6J	46.2	95	121/117M	3195/2835

TOW-MASTER ASC SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/SPEED RATING	MAX LOAD SINGLE/DUAL
THF1623580G	ST235/80R16	LRG	11.96	30.8	9.2	6.5J	57.2	110	129/125 L	4080/3640
THF1623585G	ST235/85R16	LRG	11.3	31.7	9.3	6.5J	57.2	110	132/127L	4400/3860



ENGINEERED FOR IMPROVED PERFORMANCE AND DURABILITY

Greenball's Tow-Master is one of America's most trusted trailer tire. Designed for performance and reliability, the Tow-Master fits a wide range of boat trailers, fifth wheels, toy haulers and more.

TOW-MASTER®

- Low-rolling resistance for increased fuel efficiency
- Dual steel belts and reinforced belt-edge package for strength and durability
- Speed rated for up to 81 mph
- Fits a large variety of boat, horse, ski, fifth wheels, cargo, travel trailers and more

TOW-MASTER SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX/ SPEED RATING	MAX LOAD SINGLE/DUAL
TR13175C	ST175/80R13	LRC	9	24.0	7	5J	15.5	50	91/87M	1360/1200
TR14205D	ST205/75R14	LRD	10	27.1	8	5 1/2J	21.8	65	105/101M	2040/1820
TR14215D	ST215/75R14	LRD	10	26.7	8.5	6J	23.4	65	108/103M	2200/1930
TR15205D	ST205/75R15	LRD	10	27.1	8	5 1/2J	23.5	65	107/102M	2150/1870
TR15225E	ST225/75R15	LRE	10	28.3	8.8	6J	28.0	80	117/112M	2830/2470
TR16235E	ST235/80R16	LRE	10	30.8	9.3	6 1/2J	32.6	80	124/120M	3520/3080
TR1623585F	ST235/85R16	LRF	10	31.7	9.3	6 1/2J	37.6	95	128/124M	3960/3250



OUR ECONOMICAL SPECIAL TRAILER TIRE LINE

TRANSmaster EV[®]

- High quality, solid construction
- Available in 7 sizes
- Radial design
- Speed rated M
- Four circumferential grooves for better water evacuation and traction



TRANSMaster EV SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	LOAD INDEX / SPEED RATING	MAX LOAD SINGLE/DUAL
TF13175C	ST175/80R13	LRC	9	24	7	5J	15.5	50	91/87M	1360/1200
TF14205D	ST205/75R14	LRD	10	27.1	8	5.5J	21.8	65	105/101M	2040/1820
TF15205C	ST205/75R15	LRC	10	27.1	8	5.5J	22.3	50	101/97M	1820/1610
TF15205D	ST205/75R15	LRD	10	27.1	8	5.5J	23.5	65	107/102M	2150/1870
TF15225E	ST225/75R15	LRE	10	28.3	8.8	6J	28.0	80	117/112M	2830/2470
TF16235E	ST235/80R16	LRE	10	30.8	9.3	6.5J	32.6	80	124/120M	3520/3080
TF1623585F	ST235/85R16	LRF	10	31.7	9.3	6.5J	37.7	95	128/124M	3960/3520

TRANSmaster[®]

- Two steel cord belts for added strength and vehicle stability.
- Extra load-carrying capacity compared to non-ST tires.



TRANSMaster SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	LOAD INDEX / SPEED RATING	MAX LOAD SINGLE/DUAL
TT14215C	ST215/75R14	LRC	9	26.7	8.3	6	21.4	50	102L	1870
TT16235E	ST235/80R16	LRE	10	30.9	9.3	6.5	37.1	80	124/120L	3500/3080



A GREAT VALUE AT A GREAT PRICE POINT

MIRAGE

- Dependable towing performance and traction.
- For use on a wide variety of boat, utility, fifth wheel, travel, horse, utility trailers and more.

MIRAGE SPECIAL TRAILER RADIAL

PART #	SIZE	PLY RATING	TREAD DEPTH 32ND INCH	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	LOAD INDEX / SPEED RATING	MAX LOAD SINGLE/DUAL
TMG13175C	ST175/80R13	LRC	9	24.0	7	5J	15.4	50	91/87M	1360/1200
TMG14205C	ST205/75R14	LRC	10	27.1	8	5.5J	20.5	50	100/96M	1760/1570
TMG14205D	ST205/75R14	LRD	10	27.1	8	5.5J	21.8	65	105/101M	2040/1820
TMG14215C	ST215/75R14	LRC	10	26.7	8.5	6J	22	50	102/98M	1870/1650
TMG14215D	ST215/75R14	LRD	10	26.7	8.5	6J	23.4	65	108/103M	2200/1930
TMG15205C	ST205/75R15	LRC	10	27.1	8	5.5J	22.3	50	101/97M	1820/1610
TMG15205D	ST205/75R15	LRD	10	27.1	8	5.5J	23.4	65	107/102M	2150/1870
TMG15225D	ST225/75R15	LRD	10	28.3	8.8	6J	26.7	65	113/108M	2540/2200
TMG15225E	ST225/75R15	LRE	10	28.3	8.8	6J	28.4	80	117/112M	2830/2470
TMG16235E	ST235/80R16	LRE	10	30.8	9.3	6.5J	32.5	80	124/120M	3520/3080
TMG1623585F	ST235/85R16	LRF	10	31.7	9.3	6.5J	37.7	95	128/124M	3960/3520



SPECIAL TRAILER RADIAL TIRE AND WHEEL ASSEMBLIES AVAILABLE



SPECIAL TRAILER RADIAL TIRE AND WHEEL ASSEMBLIES

PART #	SIZE	STYLE	WHEEL FINISH	WHEEL SIZE	BOLT PATTERN	LOAD RANGE	WEIGHT LBS.	MAX LOAD
TR13175C-WS1345MW	ST175/80R13	MODULAR	WHITE	13X4.5	5-4.5	6PR	28.3	1360/1201
TR13175C-WS1345SW	ST175/80R13	SPOKE	WHITE	13X4.5	5-4.5	6PR	28.3	1360/1201
TMG14205C-WS1455MW	ST205/75R14	MODULAR	WHITE	14X5.5	5-4.5	6PR	38.1	1760/1570
TMG14205C-WS1455SW	ST205/75R14	SPOKE	WHITE	14X5.5	5-4.5	6PR	37.7	1760/1570
TMG15205C-WS1555MW	ST205/75R15	MODULAR	WHITE	15X5	5-4.5	6PR	40.6	1820/1650
TMG15205C-WS1565SW	ST205/75R15	SPOKE	WHITE	15X6	5-4.5	6PR	41.1	1820/1650
TR15225E-WS1566MWS	ST225/75R15	MODULAR	WHITE	15X6	6-5.5	10PR	50.0	2830
TR15225E-WS1566SW	ST225/75R15	SPOKE	WHITE	15X6	6-5.5	10PR	50.0	2830
TR16235E-WS1606MW	ST235/80R16	MODULAR	WHITE	16X6	6-5.5	10PR	62.2	3520/3086
TR16235E-WS1606SW	ST235/80R16	SPOKE	WHITE	16X6	6-5.5	10PR	61.7	3520/3086
TR1623585F-WY1608MWH	ST235/85R16	MODULAR	WHITE	16X6	8-6.5	12PR	64.2	3960/3527

Other tire and wheel combinations available, including our Transmaster, Transmaster EV lines, and Mirage lines. Please contact Account Services for details.



TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TD 32nds. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T0854E	4.80-8	LRB	S380	7	16.5	4.7	3.75	4.9	60	590
T0856E	4.80-8	LRC	S380	7	16.5	4.9	3.75	5.1	90	760



TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TD 32nds. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T0864E	5.70-8	LRC	S378	9	18.3	5.6	3.75	8.1	75	910
T0865E	5.70-8	LRD	S378	6.8	18.6	5.5	3.75	8.0	100	1070
T0914E	6.00-9	LRC	S252	9.2	20.8	6.2	4	11.6	60	1120
T1214E	4.80-12	LRC	S378	9	20.8	5	4	8.7	90	990
T1228E	5.30-12	LRC	S378	9	21.9	5.4	4	10.1	80	1045



TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TD 32nds. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T0874E	18.5X8.50-8	LRC	S368	7.6	18.2	8.4	7	11.1	50	940
T0890E	16.5X6.50-8	LRC	S368	6.6	16.3	6.6	5.375	8.1	70	795
T1026E	20.5X8.00-10	LRC	S368	10	20.6	7.8	6	14.5	50	1105
T1028E	20.5X8.00-10	LRD	S368	10	20.8	7.8	6	14.3	70	1330
T1030E	20.5X8.00-10	LRE	S368	10	20.8	7.8	6	16.3	90	1535
T1032E	20.5X8.00-10	LRF	S368	10	20.6	7.8	6	17.8	110	1735



TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T0854C	4.80-8	LRB	HT329	7	16.6	4.75	3.75	6.17	58	590
T0856C	4.80-8	LRC	HT329	7	16.6	4.75	3.75	5.5	90	760
T1212C	4.80-12	LRB	HT329	7	20.6	4.75	3.75	7.63	60	780

TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T0874C	18.5X8.50-8	LRC	HT328	9	18.0	8.3	7	12	45	1050

TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T1222S	22.5X8.00-12	LRF	S370	9.7	22.5	8.7	7	21.3	110	1980



TOW-MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD PATTERN	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T1316C	ST175/80D13	LRC	HT326	8	24.0	6.8	5	15.4	50	1360/1200
T1415C	ST205/65D14	LRC	HT326	11	24.4	7.6	5	20	50	1760
T1424C	ST205/75D14	LRC	HT326	10	25.5	7.6	5-6	19.2	50	1760/1570
T1516C	ST205/75D15	LRC	HT326	10	27.0	7.25	5.5-6	20.5	50	1820/1610
T1528C	ST225/75D15	LRD	HT326	11	28.1	8.25	6-7	25.3	65	2540/2200



CENTENNIAL HIWAY MASTER SPECIAL TRAILER BIAS

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
T1316M	ST175/80D13	LRC	9	24	6.5	4.5	14.5	50	1360
T1424M	ST205/75D14	LRC	9	26.1	7.5	5.5	18.5	50	1760
T1516M	ST205/75D15	LRC	9	27	7.8	5.5	19.4	50	1850
T1528M	ST225/75D15	LRD	9	28.2	8.5	6	23.2	65	2540



HIWAY MASTER ST BIAS

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
ST15700D	ST205/90D15	LRD	12	29.5	7.9	5.5F	30.9	65	2600/2270
ST15700E	ST205/90D15	LRE	12	29.5	7.9	5.5F	30.9	80	2910/2540
ST16750E	ST225/90D16	LRE	12	31.7	8.5	6G	35.1	75	3440/3020

HIWAY MASTER LPT BIAS

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
L1459G	9-14.5	LRG	14	28.3	9.9	7	33.9	115	3500

TOW-MASTER LPT BIAS

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
L1479C	7-14.5 ST	LRF	7.6	26.8	7.6	6	22.5	100	2335
L1458C	8-14.5 ST	LRG	7.5	27.8	8	6	23	115	3100

HOMASTER MOBILE HOME BIAS

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
H1436R	8-14.5	LRH	9	26.5	7.5	6	21.7	115	3500
HLS14GS	215/60D14.5	LRG	9	24.3	8	6	22	110	3100
L14523560H	235/60D14.5	LRH	11	26.5	8.8	7	28.1	115	3650

**TOW-MASTER BIAS TRAILER TIRE ASSEMBLIES**

PART #	SIZE	LOAD RANGE	TREAD	STYLE	WHEEL FINISH	WHEEL SIZES	BOLT PATTERN	WEIGHT LBS.	MAX LOAD
T0856C-W0804RW	4.80-8	LRC	HT329	STAMPED	WHITE	8X3.75	4-4	10	760
T0856C-W0805RW	4.80-8	LRC	HT329	STAMPED	WHITE	8X3.75	5-4.5	9.8	760

TOW-MASTER BIAS TRAILER TIRE ASSEMBLIES

PART #	SIZE	LOAD RANGE	TREAD	STYLE	WHEEL FINISH	WHEEL SIZES	BOLT PATTERN	WEIGHT LBS.	MAX LOAD
T0864E-W0804RW	5.70-8	LRC	S378	STAMPED	WHITE	8X3.75	4-4	12.6	910
T0864E-W0805RW	5.70-8	LRC	S378	STAMPED	WHITE	8X3.75	5-4.5	12.4	910
T0865E-W0804RW	5.70-8	LRD	S378	STAMPED	WHITE	8X3.75	4-4	12.5	1070
T0865E-W0805RW	5.70-8	LRD	S378	STAMPED	WHITE	8X3.75	5-4.5	12.2	1070

TOW-MASTER BIAS TRAILER TIRE ASSEMBLIES

PART #	SIZE	LOAD RANGE	TREAD	STYLE	WHEEL FINISH	WHEEL SIZES	BOLT PATTERN	WEIGHT LBS.	MAX LOAD
T1026E-W1064RW	20.5X8.00-10	LRC	S368	STAMPED	WHITE	10X6	4-4	24.5	1105
T1026E-W1065RW	20.5X8.00-10	LRC	S368	STAMPED	WHITE	10X6	5-4.5	24.5	1105
T1028E-W1064RW	20.5X8.00-10	LRD	S368	STAMPED	WHITE	10X6	4-4	24.3	1330
T1028E-W1065RW	20.5X8.00-10	LRD	S368	STAMPED	WHITE	10X6	5-4.5	24.3	1330
T1030E-W1065RW	20.5X8.00-10	LRE	S368	STAMPED	WHITE	10X6	5-4.5	26.3	1535
T1032E-W1065RW	20.5X8.00-10	LRF	S368	STAMPED	WHITE	10X6	5-4.5	27.8	1735



TOW-MASTER BIAS TRAILER TIRE ASSEMBLIES

PART #	SIZE	LOAD RANGE	TREAD	STYLE	WHEEL FINISH	WHEEL SIZES	BOLT PATTERN	WEIGHT LBS.	MAX LOAD
T1214E-WS1244MW	4.80-12	LRC	S378	MODULAR	WHITE	12X4	4-4	18.4	990
T1214E-WS1245MW	4.80-12	LRC	S378	MODULAR	WHITE	12X4	5-4.5	18.7	990
T1214E-WS1244SW	4.80-12	LRC	S378	SPOKE	WHITE	12X4	4-4	18.7	990
T1214E-WS1245SW	4.80-12	LRC	S378	SPOKE	WHITE	12X4	5-4.5	18.7	990
T1228E-WS1244MW	5.30-12	LRC	S378	MODULAR	WHITE	12X4	4-4	19.8	1045
T1228E-WS1245MW	5.30-12	LRC	S378	MODULAR	WHITE	12X4	5-4.5	20.1	1045
T1228E-WS1244SW	5.30-12	LRC	S378	SPOKE	WHITE	12X4	4-4	20.1	1045
T1228E-WS1245SW	5.30-12	LRC	S378	SPOKE	WHITE	12X4	5-4.5	20.1	1045

TOW-MASTER BIAS TRAILER TIRE ASSEMBLIES

PART #	SIZE	LOAD RANGE	TREAD	STYLE	WHEEL FINISH	WHEEL SIZES	BOLT PATTERN	WEIGHT LBS.	MAX LOAD
T1316C-WS1344MW	ST175/80D13	LRC	HT326	MODULAR	WHITE	13X4.5	4-4	28.2	1360
T1316C-WS1345SW	ST175/80D13	LRC	HT326	SPOKE	WHITE	13X4.5	5-4.5	28.2	1360
T1424C-WS1455MW	ST205/75D14	LRC	HT326	MODULAR	WHITE	14X5.5	5-4.5	37.1	1760
T1424C-WS1455SW	ST205/75D14	LRC	HT326	SPOKE	WHITE	14X5.5	5-4.5	36.7	1760
T1516C-WS1555MW	ST205/75D15	LRC	HT326	MODULAR	WHITE	15X5	5-4.5	39.5	1820
T1516C-W1555SW	ST205/75D15	LRC	HT326	SPOKE	WHITE	15X5	5-4.5	38.6	1820
T1528C-WS1565MW	ST225/75D15	LRD	HT326	MODULAR	WHITE	15X6	5-4.5	47.2	2540
T1528C-WS1565SW	ST225/75D15	LRD	HT326	SPOKE	WHITE	15X6	5-4.5	47.2	2540

Other tread patterns, wheel styles, finishes, and bolt patterns available. Please contact Account Services for details.



ULTRA TURF - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G63724S	15X6.00-6	4PR	6.3	14.7	6.1	4.5	5.2	30	570
G83716S	16X6.50-8	6PR	6.3	15.7	7.1	5.375	5.2	42	770
G83726S	16X7.50-8	6PR	6.3	16.4	7.3	5.375	8.2	32	815
G83746S	18X8.50-8	6PR	7.6	18	8.5	7	9.9	34	1050
G83756S	18X9.50-8	6PR	8.2	18.7	9.3	7	10.5	36	1320
G83776S	20X10.00-8	6PR	9.1	19.8	10.3	7	13.6	34	1540
G1036	20X10.00-10	6PR	10	19.7	9.6	8	15.8	32	1450
G12936S	23X8.50-12	6PR	12.3	22.7	8.5	7	15.7	34	1445
*G12946S	23X10.50-12	6PR	12.5	22.8	10.4	8.5	18.7	32	1760
G12984S	26X12.00-12	4PR	9	25.8	12.8	10.5	28.2	24	1764

*Meets and exceeds DOT standards.



SAWTOOTH - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G4424S	4.10/3.50-4	4PR	5	10.4	3.9	2.5	2.3	50	350
G5224S	4.10/3.50-5	4PR	5	11.7	3.7	3.25	2.5	50	380
G6324S	4.10/3.50-6	4PR	5	12.7	3.7	3.25	3	50	445



SOFT TURF - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G4522S	11X4.00-4	2PR	5	11.02	4.01	2.75	2.6	24	215
G5524S	11X4.00-5	4PR	4	10.5	3.9	2.50	2.95	46	330
G6724S	13X5.00-6	4PR	6	12.7	4.5	3.25	4	40	440
G6942S	13X6.50-6	4PR	6	13.1	6.3	4.5	5.2	28	460
G6562S	15X6.00-6	4PR	6	14.7	6.1	4.5	5.37	30	570
G8762S	16X6.50-8	4PR	9	16.2	6.3	5.375	6.4	28	620
G8832S	18X8.50-8	4PR	9	18	8.6	7	11	22	814
G8882S	18X9.50-8	4PR	9	18.5	9	7	12	24	1038
G8514S	20X8.00-8	4PR	8	19.5	8.8	7	10.7	22	945
G1024S	20X10.00-10	4PR	8.1	20	9.4	8	13.2	22	1170
G1214S	23X8.50-12	4PR	8.9	22.6	8.4	7	15.4	22	1100

UNIVERSAL - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	PSI	MAX LOAD
T0868P	5.70-8	8PR	12	18.9	5.9	4.5	9.5	100		1075



STUD - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G4224S	4.10/3.50-4	4PR	5	10.6	3.7	2.5	2.4	50	352
G5124S	4.10/3.50-5	4PR	5	11.7	3.8	3.75	3	50	380
G6124S	4.10/3.50-6	4PR	5	12.7	3.8	3.75	2.8	50	445
G8242S	4.80/4.00-8	4PR	7	16.2	4.8	3.75	4.6	50	670



RIB - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G5544S	11X4.00-5	4PR	4	10.6	4	3.25	2.8	46	326
G6752S	13X5.00-6	4PR	4	12.4	4.6	3.5	3.2	40	440
G6922S	13X6.50-6	4PR	5	12.8	5.9	4.25	5.2	28	308
G6802S	15X6.00-6	4PR	5	14.4	6	4.25	5	30	352
G8802S	16X6.50-8	4PR	7	16.2	6.7	5.375	5.7	28	620
G8842S	18X8.50-8	4PR	7	17.7	8.4	7	8.9	22	815
G1074	20X10.00-10	4PR	10	19.7	9.6	8	11.3	22	1170



SMOOTH



WHEEL BARROW - LAWN AND GARDEN

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G8362S	3.50-8	2PR	4	15	3.5	2.5	2.0	30	320
G8142S	4.80/4.00-8	4PR	4	15.9	4.3	2.5	2.6	50	484
G8182S	4.80/4.00-8	4PR	SMOOTH	16	8	2.5	3.0	50	670



GOLF CART - SAWTOOTH

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G8852R	18X8.50-8	4PR	8	18	8.5	7	8.9	22	815
G8852D	18X8.50-8	4PR	8	17.9	8.1	7	10.1	22	505*

All golf tires meet and exceed DOT standards.

*G8852D available in 815 maxload upon request



GREENSAVER PLUS - GOLF CART

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G8852C	18X8.50-8	4PR	9	17.7	8.3	7	9.9	22	815



GREENSAVER PLUS G/T - GOLF CART

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G0802	215/60-8	4PR	8	18.5	8.8	7	9.6	35	780
G1004	205/50-10	4PR	8	18	8.4	7	11.7	30	675
G1005	205/65-10	4PR	9	20	8.3	7	11.8	35	910
G1206	205/30-12	4PR	8	17.7	7.6	7	9.5	12	465
G1215	215/50-12	4PR	10	20.6	8.4	7	15.3	35	910
G1406	205/30-14	4PR	9	21	7	6	11.5	25	925



GREENSAVER PLUS G/T PERFORMANCE RADIAL - GOLF CART

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
G1207	215/35R12	4PR	8	18.2	8	7	11	22	450/700

All golf tires meet and exceed DOT standards.



GREENSAVER PLUS

GREENSAVER PLUS G/T



GOLF CART TIRE & WHEEL ASSEMBLIES

PART #	SIZE	WHEEL STYLE	WHEEL FINISH	WHEEL SIZE	BOLT PATTERN	LOAD RANGE	WEIGHT LBS.	MAX LOAD
SAWTOOTH								
G8852D-W8704W	18x8.50-8	STAMPED	WHITE	8X7	4-4	4PR	16.1	505
G8852D-W8704A	18x8.50-8	STAMPED	ALMOND	8X7	4-4	4PR	16.1	505
G8852R-W8704W	18X8.50-8	STAMPED	WHITE	8X7	4-4	4PR	14.9	815
G8852R-W8704A	18X8.50-8	STAMPED	ALMOND	8X7	4-4	4PR	14.9	815
GREENSAVER PLUS								
G8852C-W8704W	18x8.50-8	STAMPED	WHITE	8X7	4-4	4PR	15.9	815
G8852C-W8704A	18x8.50-8	STAMPED	ALMOND	8X7	4-4	4PR	15.9	815
GREENSAVER PLUS/GT								
G0802-W8704W	215/60-8	STAMPED	WHITE	8X7	4-4	4PR	15.6	780
G0802-W8704A	215/60-8	STAMPED	ALMOND	8X7	4-4	4PR	15.6	780

All golf tires meet and exceed DOT standards.

Other steel and aluminum wheel styles available. Please contact Account Services for details.

G8852D available in 815 max load upon request.

GBC[®]

POWERSPORTS TIRES

UTV/ATV TIRES



GBC TIRE PERFORMANCE CHART

TIRE	SPORT ATV	UTILITY ATV	UTV/ SXS	ROCKY TRAIL/ DESERT	GENERAL TRAIL/ RIDING	SOFT TERRAIN	DEEP MUD	DUNES/ LOOSE SAND	X-COUNTRY RIDING	MX CLOSED COURSE	STREET/ HARD SURFACE
KANATI TERRA MASTER											
KANATI MONGREL											
GRIM REAPER											
SPARTACUS											
DIRT COMMANDER											
DIRT TAMER											
DIRT DEVIL											
AFTERBURN											
AFTERBURN STREET FORCE											
XC - MASTER											
MINI MASTER											
XC - RACER											
GROUND BUSTER III											
MINI MONGREL											
BATTLE-BORN											

 EXCEPTIONAL PERFORMANCE
  VERY GOOD PERFORMANCE



CUSTOMIZABLE SET UP FOR MAXIMUM PERFORMANCE

TERRA MASTER

- Asymmetrical tread pattern for dual benefits and performance characteristics
- Steel belted radial design for stronger core and greater wear resistance
- 10-Ply rated construction
- Meets and exceeds DOT standards
- Non-directional for excellent responsiveness in any direction

SIDE A

Recommended mounted out for soft to intermediate terrain

SIDE B

Recommended mounted out for intermediate to hard terrain

GBC TERRA MASTER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122709TM	27X9.00R12	10PR	17.9	27.2 on 6.0	8.5	6-7	29.3	20	760
AE122711TM	27X11.00R12	10PR	17.9	27.4 on 8.0	10.2	7-9	31.0	20	855
AE142610TM	26X10.00R14	10PR	15.6	26 on 7.0	9.5	6-8	27.9	20	740
AE142709TM	27X9.00R14	10PR	17.5	27.4 on 6.0	8.5	5-7	29.0	20	715
AE142710TM	27X10.00R14	10PR	17.5	27.4 on 7.0	9.5	6-8	29.5	20	785
AE142711TM	27X11.00R14	10PR	17.5	27.5 on 8.0	10.2	7-9	31.9	20	855
AE142810TM	28X10.00R14	10PR	17.3	28.2 on 7.0	9.3	6-8	31.2	20	855
AE142910TM	29X10.00R14	10PR	17.3	28.9 on 7.0	9.3	6-8	33.0	20	880
AE143010TM	30X10.00R14	10PR	17.3	30.5 on 7.0	9.3	6-8	35.4	20	935
AE143110TM	31X10.00R14	10PR	17.3	31 on 7.0	9.3	6-8	37.2	20	990
AE143210TM	32X10.00R14	10PR	17.3	32.3 on 7.0	9.4	6-8	41.1	20	990
AE153010TM	30X10.00R15	10PR	17.3	30.4 on 7.0	9.2	6-8	35.4	20	910
AE153110TM	31X10.00R15	10PR	17.3	31 on 7.0	9.4	6-8	37.0	20	990
AE153210TM	32X10.00R15	10PR	17.3	32.3 on 7.0	9.5	6-8	39.8	20	1050
AE153310TM	33X10.00R15	10PR	17.3	32.9 on 7.0	9.6	6-8	41.1	20	1140
AE153510TM	35X10.00R15	10PR	17.4	34.9	9.9	6-8	47.0	20	1235

True specifications achieved after mounting for 24-72 hours.



CHAMPIONSHIP PROVEN PERFORMANCE



- Meets and exceeds DOT standards
- Aggressive tread for superior traction
- 10-Ply rated
- Designed for all types of terrain

GBC MONGREL ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AM122310MG	23X10.00R12	6PR	13	23.3 on 7.0	9.6	6-8	22.5	20	615
AM122508MG	25X8.00R12	10PR	20	25.3 on 7.0	8.19	5-7	23.7	20	600
AM122510MG	25X10.00R12	10PR	20	25.3 on 7.0	9.45	6-8	27.0	20	715
AM122610MG	26X10.00R12	10PR	21	26.4 on 7.0	9.1	6-8	28.6	20	760
AM122709MG	27X9.00R12	10PR	20	27.3 on 7.0	8.9	6-7	28.7	20	760
AM122711MG	27X11.00R12	10PR	20	27.4 on 7.0	10.2	7-9	31.4	20	855
AM142610MG	26X10.00R14	10PR	17	25.9 on 7.0	9.6	6-8	26.4	20	740
AM142709MG	27X9.00R14	10PR	20	27.4 on 7.0	8.7	6-7	28.0	20	715
AM142711MG	27X11.00R14	10PR	19.5	27.6 on 7.0	9.7	7-9	30.8	20	855
AM142810MG	28X10.00R14	10PR	19.5	28.5 on 7.0	9.1	6-8	31.0	20	855
AM143010MG	30X10.00R14	10PR	19.5	30.6 on 7.0	9.4	6-8	36.8	20	935
AM143210MG	32X10.00R14	10PR	19.5	32.5 on 8.0	10.1	6-8	40.7	20	1070
AM152810MG	28X10.00R15	10PR	20	28.7 on 7.0	9.3	6-8	29.6	20	825
AM153010MG	30X10.00R15	10PR	19	30.7 on 7.0	9.0	6-8	37.8	20	910
AM153210MG	32X10.00R15	10PR	19	32.4 on 7.0	9.6	6-8	41.5	20	1050

True specifications achieved after mounting for 24-72 hours.



UNCOMPROMISED PERFORMANCE AND TRACTION



- 8-Ply rated radial construction
- Deep wrap-around lugs
- Superior performance in softer terrain
- High resistance to punctures



GBC GRIM REAPER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122508GR	25X8.00R12	8PR	27	25.0 on 7.0	8.3	5-7	21.9	7/12	340/480
AE122510GR	25X10.00R12	8PR	27	25.0 on 7.0	9.4	6-8	25.8	7/12	420/580
AE122609GR	26X9.00R12	8PR	27	26.0 on 7.0	9.6	6-7	27.1	7/12	440/595
AE122611GR	26X11.00R12	8PR	27	26.0 on 7.0	10.8	7-9	32.7	7/12	520/735
AE142609GR	26X9.00R14	8PR	29	26.2 on 7.0	8.3	6-7	26.5	7/14	700/1000
AE142611GR	26X11.00R14	8PR	29	26.2 on 8.0	10.7	7-9	31.5	7/14	730/1045
AE142709GR	27X9.00R14	8PR	29	27.0 on 7.0	9	6-7	27.9	7/14	750/1075
AE142711GR	27X11.00R14	8PR	29	27.0 on 7.0	10.4	7-9	32.6	7/14	780/1120
AE142810GR	28X10.00R14	8PR	29	28.0 on 7.0	9.6	6-8	31.5	20	1200
AE143010GR	30X10.00R14	8PR	29	30.0 on 7.0	9.6	6-8	36.2	20	1360
AE143210GR	32X10.00R14	8PR	29	32.0 on 7.0	9.8	6-8	41.8	20	1520

True specifications achieved after mounting for 24-72 hours.



LEADING THE WAY THROUGH TOUGH TERRAINS



- Super tough and puncture resistant
- 8-Ply rated bias construction
- Deep sipes for greater traction
- Biting edges for greater stability and control

GBC DIRT COMMANDER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122508DC	25X8.00-12	8PR	27	25.2 on 7.0	8.2	5-7	20.5	7/12	340/480
AE122510DC	25X10.00-12	8PR	27	25.2 on 7.0	9.5	6-8	25.9	7/12	420/580
AE122609DC	26X9.00-12	8PR	27	25.7 on 7.0	8.75	6-7	23.7	7/12	410/570
AE122611DC	26X11.00-12	8PR	27	25.8 on 7.0	10	7-9	27.1	7/12	480/680
AE122709DC	27X9.00-12	8PR	26	27.7 on 6.0	8.5	6-7	25	20	750/920
AE122711DC	27X11.00-12	8PR	26	27.8 on 8.0	10.6	7-9	29.3	20	780/960
AE122810DC	28X10.00-12	8PR	27	27.9 on 7.0	9.6	6-8	29.3	20	855
AE142609DC	26X9.00-14	8PR	27	26.0 on 7.0	8.5	6-7	23.4	7/14	700/1000
AE142611DC	26X11.00-14	8PR	27	26.0 on 7.0	9.7	7-9	28.2	7/14	730/1045
AE142709DC	27X9.00-14	8PR	27	27.0 on 7.0	8.5	6-7	24.6	20	750/1075
AE142711DC	27X11.00-14	8PR	27	27.0 on 7.0	10	7-9	29.4	20	780/1120
AE142909DC	29X9.00-14	8PR	26	29.5 on 6.0	8.5	5-7	28.2	20	925
AE142911DC	29X11.00-14	8PR	26	29.6 on 8.0	10.4	7-8	33	20	985
AE143010DC	30X10.00-14	8PR	26	30.6 on 7.0	9.8	6-8	33.7	20	1050
AE143210DC	32X10.00-14	8PR	27	32 on 7.0	9.6	6-8	36.2	20	1070
AE153010DC	30X10.00-15	8PR	26	30.8 on 7.0	9.5	6-8	38	20	890

GBC DIRT COMMANDER RADIAL CONSTRUCTION (OEM REPLACEMENT)

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AER122709DC-Y	27X9.00-R12	8PR	26	27.24	8.46	6-7	28.60	12	341
AER122711DC-Y	27X11.00-R12	8PR	26	27.36	10.6	7-9	32.78	14	440

True specifications achieved after mounting for 24-72 hours.



CONQUER MUD AND OTHER CHALLENGING TERRAINS



- Deep lugs for efficient clean-out
- Added blocks for greater ground contact
- Directional tread for better forward traction
- 8-Ply rated radial construction



GBC SPARTACUS ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122508SP	25X8.00R12	8PR	27	25.0 on 7.0	8.3	5-7	22.1	7/12	340/480
AE122510SP	25X10.00R12	8PR	27	25.0 on 7.0	9.4	6-8	25.3	7/12	420/580
AE122610SP	26X10.00R12	8PR	27	25.0 on 7.0	9.6	6-8	27.4	7/12	440/595
AE122612SP	26X12.00R12	8PR	27	26.0 on 7.0	10.8	8-10	31.4	7/12	520/735
AE142709SP	27X9.00R14	8PR	29	27.0 on 7.0	9	6-7	27.4	7/14	750/1075
AE142711SP	27X11.00R14	8PR	29	27.0 on 7.0	10.4	7-9	33.3	7/14	780/1120
AE142810SP	28X10.00R14	8PR	29	27.9 on 7.0	9.6	6-8	31.3	20	1200
AE143010SP	30X10.00R14	8PR	29	30.0 on 7.0	9.6	6-8	35.6	20	1360
AE143210SP	32X10.00R14	8PR	29	32.0 on 7.0	9.8	6-8	39	20	1520

True specifications achieved after mounting for 24-72 hours.



TIME TESTED RELIABILITY



- Economical upgrade
- Great traction in various terrains
- Wide range of popular sizes



GBC DIRT DEVIL ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
AR0898	22X11.00-8	6PR	20	22.3 on 8.5	10.9	7-9	21.5	7	395
AR0937	22X11.00-9	6PR	20	22.5 on 8.0	10.8	7-9	21.6	7	395
AR0938	25X12.00-9	6PR	20	25.2 on 9.5	11.6	8-10	23.9	7	496
AR1028	22X8.00-10	6PR	20	21.9 on 5.5	8	5-7	14.2	7	275
AR1018	22X11.00-10	6PR	20	22.2 on 9.0	10.7	7-9	19.9	7	385
AR1029	23X8.00-10	6PR	20	23.4 on 5.5	8.3	5-7	15.4	7	300
AR1019	23X10.00-10	6PR	20	23.4 on 10.0	10.2	6-8	19.8	7	375
AR1060	24X11.00-10	6PR	20	24.0 on 8.0	11.1	7-9	22.3	7	440
AR1068	25X12.00-10	6PR	20	24.8 on 9.0	11.7	8-10	24.9	7	495
AR1160	23X8.00-11	6PR	20	23.4 on 7.0	7.6	5-7	14.5	7	290
AR1104	24X8.00-11	6PR	20	24.0 on 7.0	8.1	5-7	17.4	7	320
AR1103	24X9.00-11	6PR	20	23.8 on 7.0	8.6	6-7	19.1	7	365
AR1161	24X10.00-11	6PR	20	24.2 on 7.0	10.1	6-8	21.4	7	395
AR1165	25X10.00-11	6PR	20	25.2 on 7.0	10	6-8	23.1	7	430
AR1228	25X8.00-12	6PR	20	25.2 on 7.0	8.3	5-7	19.3	7	340
AR1230	25X10.00-12	6PR	20	24.4 on 7.0	9.9	6-8	20.2	7	420
AR1201	26X10.00-12	6PR	39	25.9 on 7.0	9	6-8	24.4	7	460
AR1202	26X12.00-12	6PR	39	25.9 on 8.0	11.4	8-10	30.8	7	520
AR1212	27X12.00-12	6PR	39	26.9 on 8.0	11.4	8-10	32	7	550

True specifications achieved after mounting for 24-72 hours.



ALL TERRAIN DURABILITY AND CONTROL



- Exceptional traction in all terrains
- Extended shoulder lugs for added protection
- Popular non-directional tread design
- 6-Ply rated durable bias construction



GBC DIRT TAMER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AR122816	25X8.00-12	6PR	28	25.0 on 7.0	8	5-7	21.7	7	340
AR122916	25X9.00-12	6PR	28	25.0 on 7.0	8.7	6-7	23.2	7	385
AR122926	26X9.00-12	6PR	28	26.0 on 7.0	9	6-7	25.1	7	410
AR122216	26X12.00-12	6PR	28	26.0 on 9.0	10	8-10	28.7	7	520
AR122936	27X9.00-12	6PR	28	27.0 on 7.0	9	6-7	27.6	7	440
AR122710	27X10.00-12	6PR	28	27.0 on 9.0	10	6-8	30.9	7	550
AR122711	27X11.00-12	6PR	28	27	10.7	7-9	31.4	7	550

True specifications achieved after mounting for 24-72 hours.



- Designed for smooth and comfortable ride
- Ideal for straight line racing and high speed cornering
- Balanced construction for light weight durability



GBC AFTERBURN ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122508AB	25X8.00R12	6PR	17	25.4 on 7.0	8.4	5-7	17.4	7	340
AE122510AB	25X10.00R12	6PR	17	25.4 on 7.0	9.4	6-8	22.8	7	420
AE122608AB	26X8.00R12	6PR	17	26.0 on 7.0	8.3	5-7	18.6	7	460
AE122610AB	26X10.00R12	6PR	17	26.0 on 7.0	9.4	6-8	23.1	7	560

True specifications achieved after mounting for 24-72 hours.



- Meets and exceeds DOT standards for street use
- Aggressive tread for both wet and dry conditions



GBC AFTERBURN STREET FORCE ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE122508SF	25X8.00R12	4PR	10	24.9 on 7.0	8.1	5-7	19.9	15	500
AE122510SF	25X10.00R12	4PR	10	24.6 on 8.0	10	6-8	21.7	12	500
AE142609SF	26X9.00R14	4PR	10	26.1 on 8.0	8.6	6-7	21.8	18	725
AE142611SF	26X11.00R14	4PR	10.5	26 on 8.0	10.7	7-9	25.8	18	850
AE142709SF	27X9.00R14	4PR	10	27.1 on 8.0	8.6	6-7	22.9	18	750
AE142711SF	27X11.00R14	4PR	10.5	27 on 8.0	10.7	7-9	27.1	18	850

True specifications achieved after mounting for 24-72 hours.



MINI MONGREL

- Built specifically for youth side by side applications
- Aggressive tread for maximum traction on a variety of terrains
- Narrower front engineered for optimal handling
- Rear size offers a wider contact patch for improved drive power

GBC MINI MONGREL ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
AM102307MJ	23X7.00R10	6PR	15	22.9	6.9	5.5	16.4	7	275
AM102308MJ	23X8.00R10	6PR	15	22.9	8	6.5	17.7	7	310

True specifications achieved after mounting for 24-72 hours.



- Built specifically for youth side by side applications
- Designed for the competitive racer
- Directional designed grooved X-knob for front and rear applications
- Front tire engineered for optimal handling and control
- Rear tire engineered for optimal drive and breaking

GBC BATTLE BORN ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
AE102307BB	23X7.00-10	4PR	15	22.8	6.8	5.0	13.51	7	275
AE102308BB	23X8.00-10	4PR	15	23.0	7.8	6.0	13.87	7	310

True specifications achieved after mounting for 24-72 hours.



- Improved profile for better steering and control
- Superior handling and traction
- Preferred for X-Country terrain
- GBC's most popular XC tire

GBC XC-MASTER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AR092011XM	20X11.00-9	6PR	15	20.0 on 9.0	11	7-9	16.9	7	341
AR092211XM	22X11.00-9	6PR	15	22.0 on 9.0	11.2	7-9	19.8	7	397
AR102011XM	20X11.00-10	6PR	15	20.0 on 8.0	10.8	7-9	17.6	5	330
AR102107XM	21X7.00-10	6PR	15	21.3 on 5.5	7	3.5-5.5	12	7	235
AR102207XM	22X7.00-10	6PR	15	22.0 on 5.5	6.9	3.5-5.5	13.7	7	255
AR102211XM	22X11.00-10	6PR	15	22.4 on 8.0	10.8	7-9	19.2	7	386
AR102307XM	23X7.00-10	6PR	15	23.0 on 5.5	7	3.5-5.5	13.8	7	275

True specifications achieved after mounting for 24-72 hours.

GROUND BUSTER III

- Developed in conjunction with elite GNCC ATV Pro Riders
- Designed for intermediate to hard terrain racing
- 2-Ply rated version designed for use with flat prevention systems
- 6-Ply rated version designed for greater puncture resistance



GBC GROUND BUSTER III ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AR092011GBA	20X11.00-9	2PR	16.4	20.59	10.75	7-9	14.9	7	240
AR092011GBC	20X11.00-9	6PR	16.4	20.67	10.71	7-9	15.5	7	340

True specifications achieved after mounting for 24-72 hours.



- Reinforced bead for added strength
- Multi-tiered pre-grooved knobs
- Perfect for X-country racing



GBC XC-RACER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE092011XR	20X11-9	6PR	15/32	19.6 on 9.0	11	7-9	16.5	7	350
AE102107XR	21X7-10	6PR	15/32	20.8 on 5.5	7	3.5-5.5	12	7	250

True specifications achieved after mounting for 24-72 hours.

MINI MASTER

- Engineered for Mini ATV XC and ATV MX applications
- X-type lug for better hook up and traction
- Soft yet durable compound to help conform to surfaces and terrain



GBC MINI MASTER ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH RANGE	WEIGHT	PSI	MAX LOAD
AE081808MM	18X8.00-8	2PR	15	18	8.3	7	11.5	5	182
AE081810MM	18X10.00-8	4PR	15	18	10	8	12.9	10	210
AE101906MM	19X6.00-10	2PR	11	19	6.1	5	9.1	5	148
AE102006MM	20X6.00-10	4PR	11	20	6.1	5	9.4	10	235

True specifications achieved after mounting for 24-72 hours.



- Tough and durable bias construction
- Non-directional all-terrain tread pattern
- Economical replacement tire

CENTENNIAL TERRA-X ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
AQ1003	24X11.00-10	6PR	19	24	11	9	28.7	7	440

True specifications achieved after mounting for 24-72 hours.



- Aggressive directional tread for better traction and control
- Wide open grooves promote excellent clean-out
- 6-ply rated economical replacement tire

CENTENNIAL DIRT DEVIL EV ATV/UTV

PART #	SIZE	PLY RATING	TREAD DEPTH 32NDS. IN.	O.D.	S.W.	RIM WIDTH	WEIGHT	PSI	MAX LOAD
AQ1060	24X11.00-10	6PR	25	24	11	9	26.5	7	440
AQ1068	25X12.00-10	6PR	25	25	11.4	10	30.9	7	495
AQ1103	24X9.00-11	6PR	25	24	9	7	23.1	7	365
AQ1161	24X10.00-11	6PR	25	24	9.6	8	24.7	7	395
AQ1203	26X9.00-12	6PR	20	26	8.9	7	21.6	7	410
AQ1204	26X11.00-12	6PR	20	26.1	11	9	23.1	7	480
AQ1228	25X8.00-12	6PR	19	25.2	7.9	7	18.1	7	340
AQ1230	25X10.00-12	6PR	20	25.4	9.4	7	21.6	7	420

True specifications achieved after mounting for 24-72 hours.



ULTRA 226 MACHINE SATIN BLACK ALUMINUM TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT	MAX LOAD (LB)
226-56655B	15X6	SATIN BLACK & CLEAR COAT	SPOKE	6-5.5	4.13"	0	24	3200
226-665865B	16X6.5	SATIN BLACK & CLEAR COAT	SPOKE	8-6.5	4.92"	0	27	4400



ULTRA 226 MACHINE GLOSS BLACK W/ DIAMOND CUT FACE ALUMINUM TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT	MAX LOAD (LB)
226-56655M	15X6	GLOSS BLACK W/DIAMOND CUT FACE	SPOKE	6-5.5	4.13"	0	24	3200
226-665865M	16X6.5	GLOSS BLACK W/DIAMOND CUT FACE	SPOKE	8-6.5	4.92"	0	27	4400

ULTRA 226 CAPS

PART #	DESCRIPTION
226-15CAPB	SATIN BLACK CAPS FOR 15X6
226-16CAPB	GLOSS BLACK CAPS FOR 16X6.5





5-LUG



6-LUG



8-LUG



GBC SLICK 580 SERIES ALUMINUM TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LB)	MAX LOAD (LB)
580-56655B	15X6J	MACHINE BLACK INLAY	SPOKE	6-5.5	4.25"	0	16	2830
580-66655B	16X6J	MACHINE BLACK INLAY	SPOKE	6-5.5	4.25"	0	19	3200
580-66865B	16X6J	MACHINE BLACK INLAY	SPOKE	8-6.5	5.15"	0	21	3960

5-LUG SILVER



8-LUG SILVER



6-LUG GUN GREY



8-LUG GUN GREY



GBC SPOKE 581 SERIES ALUMINUM TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LB)	MAX LOAD (LB)
581-55545S	15X5J	SILVER	SPOKE	5-4.5	3.19"	0	18	2150
581-56655S	15X6J	SILVER	SPOKE	6-5.5	4.25"	0	18	2830
581-56655G	15X6J	GUN GREY	SPOKE	6-5.5	4.25"	0	18	2830
581-66655S	16X6J	SILVER	SPOKE	6-5.5	4.25"	0	21	3200
581-66655G	16X6J	GUN GREY	SPOKE	6-5.5	4.25"	0	21	3200
581-66865S	16X6J	SILVER	SPOKE	8-6.5	5.15"	0	22	3960
581-66865G	16X6J	GUN GREY	SPOKE	8-6.5	5.15"	0	22	3960



GBC MODULAR STEEL TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	MAX LOAD (LBS)	WEIGHT (LBS)
WS1244MW	12X4JA	WHITE	MODULAR	4-4	2.65"	0	9.7	1220
WS1245MW	12X4JA	WHITE	MODULAR	5-4.5	3.19"	0	10	1220
WS1344MW	13X4.5B	WHITE	MODULAR	4-4	2.95"	0	12.8	1660
WS1345MW	13X4.5B	WHITE	MODULAR	5-4.5	3.19"	0	12.8	1660
WS1455MC	14X5.5J	CHROME	MODULAR	5-4.5	3.19"	0	17.2	1870
WS1455MW	14X5.5J	WHITE	MODULAR	5-4.5	3.19"	0	18	1870
WS1465MW	14X6J	WHITE	MODULAR	5-4.5	3.19"	0	17.8	1870
WS1555MW	15X5J	WHITE	MODULAR	5-4.5	3.19"	0	19	1870
WS1565MW	15X6J	WHITE	MODULAR	5-4.5	3.19"	0	21.8	2600
WY1565MWH	15X6J	WHITE	MODULAR	5-4.5	3.19"	0	21.8	3250
WS1566MW	15X6J	WHITE	MODULAR	6-5.5	4.28"	0	21.9	2850
WS1566MC	15X6J	CHROME	MODULAR	6-5.5	4.28"	0	21.8	2850
WS1566MWS	15X6J	WHITE	MODULAR	6-5.5	4.28"	0	22.5	2850
WS1566MWH	15X6J	WHITE	MODULAR	6-5.5	4.28"	0	21.9	3250
WS1606MW	16X6K	WHITE	MODULAR	6-5.5	4.28"	0	29.6	3760
WS1608MW	16X6K	WHITE	MODULAR	8-6.5	5.15"	0	31.2	3760
WS1608MWH	16X6K	WHITE	MODULAR	8-6.5	5.15"	0	31.2	4080
WH1608MWH	16X6K	WHITE	MODULAR	8-6.5	5.15"	0	33	4400

Standard wheels come without stripes and rivets. Stripes and rivets available upon request. All chrome wheels on this page are also clear coated.

Please contact Account Services at 800-946-9412 for specific sizes and styles of available wheels.



GBC STAR #4 ALUMINUM TRAILER WHEELS

PART #	SIZE	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	MAX LOAD (LBS)	WEIGHT (LBS.)
424545	12X4	STAR #4	5-4.5	3.19"	0	11	1520
467865	16X7	STAR #4	8-6.5	5.15"	0.2	21	3200



GALVANIZED

WHITE



GBC STAMPED STEEL TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LBS.)	MAX LOAD (LBS)
W0804RG	8X3.75	GAL	STMP	4-4	2.81"	1.875+1.875	4	1075
W0804RW	8X3.75	WHI	STMP	4-4	2.81"	1.875+1.875	4.5	1075
W0805YG	8X3.75	GAL	STMP	5-4.5	2.81"	1.875+1.875	4.3	1075
W0805RW	8X3.75	WHI	STMP	5-4.5	2.81"	1.875+1.875	4.3	1075
W0805RS	8X3.75	M.SLV	STMP	5-4.5	2.81"	1.875+1.875	4	1075
W1064RW	10X6	WHI	STMP	4-4	2.81"	3+3	10	1330
W1065RG	10X6	GAL	STMP	5-4.5	2.81"	3+3	10	1800
W1065RW	10X6	WHI	STMP	5-4.5	2.81"	3+3	10	1800
W1074RW	10X7	WHI	STMP	4-4	2.81"	3B+4	11	1200
W8504RW	8X5.375	WHI	STMP	4-4	2.81"	2.6875+2.6875	5	900
W8505RW	8X5.375	WHI	STMP	5-4.5	2.81"	2.6875+2.6875	5	900
W8704A	8X7	ALMD	STMP	4-4	2.81"	3.5+3.5	6	950
W8704RG	8X7	GAL	STMP	4-4	2.81"	3.5+3.5	6.2	950
W8704W	8X7	WHI	STMP	4-4	2.81"	3.5+3.5	6	950
W8704RB	8X7	BK	STMP	4-4	2.81"	3.5+3.5	6	950
W8705W	8X7	WHI	STMP	5-4.5	2.81"	3.5+3.5	6	950



GBC SPOKE STEEL TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LBS.)	MAX LOAD (LBS)
WS1244SG	12X4JA	GALVANIZED	SPOKE	4-4	2.65"	0	9.7	1220
WS1244SW	12X4JA	WHITE	SPOKE	4-4	2.65"	0	9.95	1220
WS1245SC	12X4JA	CHROME	SPOKE	5-4.5	3.19"	0	9.7	1220
WS1245SG	12X4JA	GALVANIZED	SPOKE	5-4.5	3.19"	0	10.2	1220
WS1245SW	12X4JA	WHITE	SPOKE	5-4.5	3.19"	0	10	1220
WS1344SG	13X4.5B	GALVANIZED	SPOKE	4-4	2.95"	0	12.8	1660
WS1344SW	13X4.5B	WHITE	SPOKE	4-4	2.95"	0	12.8	1660
WS1345SG	13X4.5B	GALVANIZED	SPOKE	5-4.5	3.19"	0	12.8	1660
WS1345SW	13X4.5B	WHITE	SPOKE	5-4.5	3.19"	0	12.8	1660
WS1455SW	14X5.5J	WHITE	SPOKE	5-4.5	3.19"	0	17.6	1870
WS1465SW	14X6J	WHITE	SPOKE	5-4.5	3.19"	0	17.8	1870
WS1555SG	15X5J	GALVANIZED	SPOKE	5-4.5	3.19"	0	18	1870
WS1555SW	15X5J	WHITE	SPOKE	5-4.5	3.19"	0	18.2	1870
WS15573SW	15X5J	WHITE	SPOKE	5-5	3.30"	0	18.5	1870
WS1565SW	15X6J	WHITE	SPOKE	5-4.5	3.19"	0	21.8	2600
WS1566SW	15X6J	WHITE	SPOKE	6-5.5	4.28"	0	22.9	2850
WS1606SG	16X6K	GALVANIZED	SPOKE	6-5.5	4.28"	0	28.9	3760
WS1606SW	16X6K	WHITE	SPOKE	6-5.5	4.28"	0	29	3760
WS1608SW	16X6K	WHITE	SPOKE	8-6.5	5.15"	0	30.3	3760

Please contact Account Services at 800-946-9412 for specific sizes and styles of available wheels.



GBC SOLID



GBC SOLID STEEL TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LBS.)	MAX LOAD (LBS)
WS1245YW	12X4JA	WHITE	SOLID	5-4.5	3.19"	0	9.8	1220
WS1344YW	13X4.5B	WHITE	SOLID	4-4	2.65"	0	12.9	1660
WS1345YW	13X4.5B	WHITE	SOLID	5-4.5	3.19"	0	12.9	1660

Standard wheels without stripes and rivets. Stripes and rivets available upon request. P = Pallet, B = Box



GBC MOBILE HOME STEEL TRAILER WHEELS

PART #	SIZE	FINISH	STYLE	WEIGHT	MAX LOAD (LB)
WS600	14.5X6MH	BLACK	MOBILE HOME	14	3200
WH700	14.5X7MH	GREY	MOBILE HOME	19.8	3500



BLACK

GOLD

BLACK INLAY

BLACK INLAY



ALUMINUM GOLF CART WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LBS.)	MAX LOAD (LBS)
AT1074MB	10X7	MCH BLACK	GOLF CART	4-4	2.69	15.5MM	7.5	400
AT107404B	10X7	BK INLAY	4 SPK SPLT	4-4	2.63"	-16MM	7.0	350
AT107404M	10X7	MACHINED	4 SPK SPLT	4-4	2.63"	-16MM	7.0	350
AT107408B	10X7	BLACK	8 SPK	4-4	2.69"	0	8.9	350
AT107410B	10X7	BK INLAY	10 SPK	4-4	2.63"	-16MM	6.0	350
AT107410M	10X7	MACHINED	10 SPK	4-4	2.63"	-16MM	6.0	350
AT127408B	12X7	BLACK	8 SPK	4-4	2.69"	0	11.0	700
AT146408B	14X6	BLACK	8 SPK	4-4	2.69"	0	12.3	800
AT146408GM	14X6	GUN METAL	8 SPK	4-4	2.69"	0	12.3	800
AT146408G	14X6	GOLD	8 SPK	4-4	2.69"	0	12.3	800

ALMOND

WHITE



STEEL GOLF CART WHEELS

PART #	SIZE	FINISH	STYLE	BOLT PATTERN	CENTER BORE	OFFSET	WEIGHT (LBS.)	MAX LOAD (LBS)
W86125W	8X6.125	WHITE	STAMPED	4-4	2.50"	1.875+4.25B	5.2	900
W8704W	8X7	WHITE	STAMPED	4-4	2.81"	3.5+3.5	6	950
W8704A	8X7	ALMOND	STAMPED	4-4	2.81"	3.5+3.5	6	950
W8704RB	8X7	BLACK	STAMPED	4-4	2.81"	3.5+3.5	6	950
W1074RW	10X7	WHITE	STAMPED	4-4	2.81"	3B+4	11	1200

Due to fluctuating market prices, please contact Account Services for wheel availability.



TRAILER WHEEL ACCESSORIES STEEL CAPS

PART #	SIZE	DESCRIPTION	MATERIAL	PKG
C-2.65	2.65"	CAP CLOSED END	CHROME	100/CTN
C-2.95	2.95"	CAP CLOSED END	CHROME	100/CTN
C-2.95OP	2.95"	CAP OPEN END	CHROME	100/CTN
63042	3.10"	CAP CLOSED END PUSH - IN	CHROME	100/CTN
C-3.195	3.195"	CAP CLOSED END	CHROME	100/CTN
C-3.195OP	3.195"	CAP OPEN END	CHROME	100/CTN
C-3.30OP	3.30"	CAP OPEN END	CHROME	100/CTN
C-3.30S	3.30"	CAP CLOSED END SHORT	CHROME	100/CTN
C-4.90	4.90"	CAP CLOSED END	CHROME	100/CTN
C-5.15	5.15"	CAP CLOSED END	CHROME	100/CTN
C-5.15OP	5.15"	CAP OPEN END	CHROME	100/CTN
C-5.15OPP	5.15"	CAP OPEN END WITH PLUG FOR 8-6.5	CHROME	100/CTN

CAP CLOSED END

CAP OPEN END

CAP FOR SMOOTHIE

CLOSED END

CAP OPEN END

ACORN LUG NUTS

TRAILER WHEEL ACCESSORIES STAINLESS STEEL CAPS

PART #	SIZE	DESCRIPTION	MATERIAL	PKG
CS-3.10	3.10"	CLOSED END	STAINLESS	100/CTN
CS-3.30	3.30"	CLOSED END	STAINLESS	100/CTN

TRAILER WHEEL ACCESSORIES SNAP ON PLASTIC CAPS

PART #	SIZE	DESCRIPTION	MATERIAL	PKG
CZ-3.10	3.10"	CAP OPEN END	PLASTIC	100/CTN
CZ-3.30	3.30"	CAP OPEN END	PLASTIC	100/CTN
CZ-3.70	3.70"	CAP OPEN END	PLASTIC	100/CTN

TRAILER WHEEL LUG NUTS ACORN-HEAT TREATED

PART #	SIZE	DESCRIPTION	MATERIAL	PKG
L1004H	1/2"	13/16 HEX 1.40" TALL, ACORN	STEEL	500/CTN
L3004	1/2"	7/8 HEX, 1.88" TALL, DUPLEX ACORN	STEEL	500/CTN

Other accessories and sizes available. Please contact Account Services for details.

GBC

POWERSPORTS TIRES



www.gbctires.com

NOTES



TERMS & CONDITIONS

- 1. Payment:** Net 30 days from invoice date on approved credit.
- 2. Shipments:** Shipments under 3000 lbs. will be freight collect.
- 3. Shipments:** Over 3000 lbs. to one location will be freight prepaid.* Any additional drop-off charge for multiple location shipments will be prepaid, with drop off charges added to the invoice.
- 4. Returns:**
 - a) No returns will be accepted unless issued a Return Authorization Number by Greenball Corporation. Material returned without authorization will not receive any credit.
 - b) Returns must be received within ten (10) days of receipt of shipment. Customer must ensure that returned products are packaged and returned in their original condition.
 - c) Non-defective material will incur a 20% restocking fee.
 - d) Special orders and discontinued items cannot be returned.
 - e) No credit can be issued until Greenball Corporation inspects returned product. Credit will be issued at original invoice price only.
- 5. Claims:** Shortage claims, error or defect in shipment must be made within 72 hours of receipt of goods. Claims for damage or loss in transit must be made directly with the carrier.
- 6. Prices:** Prices and terms subject to change without notice.
- 7. FedEx Special Handling Charge:** Oversized orders will be charged a \$7.00 additional handling fee from our standard rate.

*Weight minimum for freight prepayment subject to change due to outside (external) influences.
You may confirm minimum weight with any customer service personnel.

WARNING

Tire Mounting can be dangerous if not done by trained personnel using proper tools and equipment. For your own safety, seller recommends that users have tires and inner tubes changed by an experienced service provider.

Greenball Corporation strives to ensure the accuracy of all information contained in this catalog. However, misprints, inaccuracies, omissions and other errors may occur. Greenball Corporation does not take responsibility for any errors, misprints, omissions or any other inaccuracies found herein; including but not limited to product information specifications or item availability. All Greenball brand tires are subject to continuous development and design. Greenball Corporation reserves the right to change construction, materials, or specifications without notice of obligation.

LIMITED WARRANTY

Greenball Corporation warrants its products, to the original purchaser only, against failure due to factory defective materials and workmanship for four years from the date of manufacture, or two years from invoice date of purchase verified by the original invoice or copy thereof. All request for claims and tire inspections must be submitted through the proper Greenball Corporation Warranty channels.

*For Tow-Master® Radial series, please see Tow-Master® Radial warranty pamphlet for complete information.

Greenball Corporation makes no expressed claims of expected tire wear. Variables that effect tire wear include but not limited to driving/riding conditions, load and pressure, under/over inflation and improper mounting.

*Other limitations and exceptions apply. Please contact a Warranty Specialist for complete information.

What is not covered by the Warranty?

- Greenball Corporation does not pay for mounting, balancing, or labor. Greenball Corporation does not cover loss of time, inconvenience, loss of use of vehicle, costs of towing or transportation or consequential damages of any nature.
- Tires/wheels which have been patched, plugged or repaired or on to which liquid balancers or sealants have been applied. Patching, repairing of tires, or applying any sealants on tire will automatically VOID any warranty.
- Failure, damage or irregular wear caused by misalignment or any other mechanical causes.
- Failure, damage or irregular wear caused by driving in violation of SPEED, LOAD, or TEMPERATURE RATINGS.
- Failure due to fire, accident, malicious mischief, improper inflation, improper use, running flat, overloading or road hazards. Examples of road hazards include nails, glass and other foreign objects and natural/man-made defects or obstacles such as excavations, construction, potholes and chuckholes. Damages caused by road hazards include cuts snags, punctures, scuffs, carcass bruises and impact breaks.
- Premature or irregular wear due to improper inflation or alignment.
- Tires used in racing or competition.

For questions or to file a claim, please contact our Warranty Specialists at 1-866-767-9637.
Please see our warranty brochure for complete information.

To register your tires please visit www.greenball.com/support/tire-registration

LOCATIONS

Corporate Headquarters

222 S. Harbor Blvd. Suite 700
Anaheim, CA 92805
Tel: 714-782-3060
Fax: 714-782-7052

East Coast Distribution Center

4300 Hunter Road
Atlanta, GA 30349
Tel: 404-476-4725

West Coast Distribution & Account Services

13310 Valley Blvd.
Fontana, CA 92338
Tel: 951-361-0659
Fax: 714-782-7075

Corporate Accounts Support Center

128 E. Main St. Suite A
Union City, TN 38261
Tel: 800-946-9412
Fax: 714-782-7075

Accounts Services/Order Desk

Tel: 800-946-9412
Fax: 714-782-7075

Warranties>Returns

Tel: 866-767-9637
Fax: 714-782-7074



GREENBALL®

TIRES FOR THE ROAD, WORK, AND PLAY

